


149. Silicone hose wire reinforced

Function:

Silicone hose wire reinforced is used as flexible connections in high pressure and vacuum application in the pharmaceutical and the food industry.

Features:

- Platinum silicone
- Wire braid AISI 316L
- Flexible
- Sterilizable, Autoclavable
- Imparts no taste or odour
- Good chemical resistance
- High Pressure and vacuum applications
- Temperature range: -62 °C to 177 °C



- FDA CFR 177.2600
- European Pharmacopoeia 3.1.9
- ISO 10993
- USP VI
- 3A





ORDERING INFORMATION: ENGINEERING SOLUTIONS

Part#	ID (mm)	OD (mm)	Working pressure(kg/c m2)@20 C
149-000-000	12.7	23.37	10.3
149-000-001	19.1	30.2	8.6
149-000-002	25.4	36.8	8.6
149-000-003	38.1	54.8	8.6
149-000-004	50.8	68.3	6.89

Vacuum rating: -0.99 bar

Hose available in coils of 25 ft.

Contact our application specialist if end connections are required.

All dimensions are in mm. unless and otherwise specified. The information contained in this brochure is for guidance only. We reserve the right to modify any material or feature without notice in advance. For further information, please, consult our application specialist.

Filename: 149_Silicon hose wire reinforced

Directory: F:\M\Datasheet

Template:

C:\Users\user\AppData\Roaming\Microsoft\Templates\Normal.dot

m Title:

Subject:

Author: user

Keywords: Comments:

Creation Date: 24-01-2014 22:51:00

Change Number: 10

Last Saved On: 24-06-2014 23:29:00

Last Saved By: user
Total Editing Time: 60 Minutes

Last Printed On: 04-07-2014 08:29:00

As of Last Complete Printing
Number of Pages: 1

Number of Words: 168 (approx.)

Number of Characters: 962 (approx.)